Force Monitoring of Pre-Stressing Steel in Structures

Shahid Islam HQ Technical Services Dywidag-Systems International

PTI Convention 2014, Norfolk, VA





OUTLINE

- Introduction
- **O** Theory
- **O** Systems
- **O** Accuracy
- Measuring Procedure
- Applications
- Conclusions

INTRODUCTION

Health monitoring system

Determine the behavior of the structure under various loads and environmental effects

Know the condition of the structure before it is too late

Inspection- non-destructive testing

Repair or replacement

Post-tensioning is a key element to the performance and durability of the structures where they are installed

Tendon or stay force During construction Long-term monitoring Periodic, continuous, remote

INTRODUCTION Cont'd

Tendon embedded or external

Tendon/stay either of strand or high strength bar

Strand/bar can be of bare, coated or grouted

Various methods to measure the tendon/stay force

Most are cumbersome and accuracy differs

DSI involved in development, testing and utilization of DYNA Force sensors to measure the force in tendon/stay

THEORY

Sensors are manufactured based on the magneto-elastic properties of ferrous material.

FARADAY'S LAW: Change in magnetic environment of a coil of wire will cause a voltage to be induced in the coil



THEORY Cont'd

Sensor is composed of a primary coil and a secondary coil

By passing current through primary coil, ferromagnetic material is magnetized

Sensing coil picks up induced electromotive force that is proportional to change rate of applied magnetic flux and relative permeability

As permeability of core changes, output voltage changes

Output voltage is calibrated to measure force



SYSTEMS

DYNA Force System consists of mainly sensor and readout unit

The force can be measured by:

Manual reading Local data storage Remote access





Sensor

Multiplexer

SYSTEMS- Cont'd

Table: DYNA Force Dimensions

Strand Size	Strand Grade	Sensor Dimensions [in]		
[in]	[KSI]	ID	OD	Length
0.5" - 0.62"	270	0.79	1.42	5.2
THREADBAR Size	Bar Grade	Sensor Dimensions [in]		
[in]	[KSI]	ID	OD	Length
#7 - #11	75-97	1.69	3.15	7.09
#14	75-97	2.09	3.90	7.87
#18 / #20	75-97	2.87	5.71	12.20
#24	75-97	3.35	6.10	12.99
1" - 1-3/8"	150	1.69	3.15	7.09
1-3/4"	150	2.09	3.90	7.87
2-1/2"	150	2.87	5.71	12.20
3"	150	3.35	6.10	12.99

DYNA Force over the tendon x-section is custom made and dimensions will be provided upon request

ACCURACY

Due to the diversity of the magnetic property of steel, calibration is done for each type of steel allowing the sensors to perform at their highest accuracy.

Three sensors were used in each of three 59-0.6" strand anchors

Sensors were consistently more accurate than load cells when compared to the actual jacking force.



MEASURING PROCEDURE

Sensors supplied are pre calibrated at DSI facility

Install over the strand/bar or tendon during construction

Attach portable readout unit to wire leads from the sensor

Take a zero reading before applying any force

Apply PT/stay force

Measure the force in tendon/anchor anytime from anywhere

APPLICATION- Penobscot Narrows Bridge, Maine, USA

80 stay cable anchors with 3 sensors in each anchor- opened to traffic Dec 2006 Stay force was monitored during construction Recent sensor readings Dec 2013



APPLICATION- Penobscot Narrows Bridge, Maine, USA

Data received after the bridge 7 years in service are very consistent



APPLICATION- Harbor Drive Bridge, San Diego, USA

Sensors were installed in two foundation tie-downs, two back stays and two main cables.

Sensors enabled verification of friction assumptions and permitted adjustment to jacking forces to achieve the target force at the pylon tip. Lock-off forces in the tie-down anchors were also adjusted based on the sensor readings.





APPLICATION- Wacker Drive Bridge, Chicago, USA

Sensors were installed to know: Force at dead end of 9-06 longitudinal tendons Jacking force was revised based on finding Force at dead end of 4-06 transverse tendons Good correlation was observed







APPLICATION- Wade Bridge (I-81), Pennsylvania, USA

Twelve sensors were installed to monitor forces in 1-3/4" DCP external tendons in Pier Caps Good correlation was observed





APPLICATION- Pont Champlain Bridge, Montreal, Canada

Sensors were installed to monitor forces in 0.6" dia strands used to retrofit the exterior girders Sensors readings provided valuable Information to the designer







APPLICATION- SFO Tower

Fifty-two DF sensors were installed in 19-06 tendons (2 per anchor). All sensors were monitored during construction and will be monitored after any seismic event. Sensor readings were very consistent with jacking force.



APPLICATION- Wind Technology Testing Center-Boston, USA

Sensors were utilized to monitor the force in 1-3/4"-Gr. 150 ksi post-tension bars in the vertical wall. Forces were monitored during construction and two months after stressing. Force will be measured after Dynamic Testing is completed.





APPLICATION- Retaining Wall- Rt 405, CA

48 DYNA Force sensors were installed on tie back anchors to monitor the performance of the retaining wall. Automated readout units were installed to record the force at every 4 hrs.







APPLICATION- Sellwood Bridge Abutment, Oregon, USA

56 sensors were supplied to monitor the slope stability in front of the bridge abutment. Automated readout units were installed to record the force readings at every 4 hours.







APPLICATION- Willow Island Hydroelectric Project, WV, USA

To monitor the forces in the anchors during excavation of rocks, three sensors were installed in each of 28 anchors (59-0.6").

Data from all of the sensors are being taken remotely every 3 hours, analyzed and reported to the owner.













APPLICATION- Project in LA

Sensors in bonded and unbonded length provide valuable data to the engineer.





APPLICATION- Stone Cutters Bridge, Hong Kong

32 sensors were installed at the interfaces of steel girders and RC girders to monitor the force in 37-0.62" tendons







Courtesy- IIS

APPLICATION- Hsing-Tung Bridge, Taiwan

EM sensor was installed on stay cable Sensor was fabricated in the field by winding process Stay force is being monitored



Courtesy- IIS

APPLICATION- Adige Bridge, Italy

EM sensors were used on the existing stays A total of twelve sensors were installed Sensors were precalibrated at the laboratory All sensor reading are accessed remotely







Courtesy- IIS

CONCLUSIONS

Sensors can be used for:

bare, epoxy-coated, galvanized and greased-sheathed steel in bonded, un-bonded, grouted or un-grouted length of the tendon.

Sensors for existing tendon/stay

Eliminates any lift-offs & friction tests

Portable read-out unit

Reading in seconds by a trained person

Owner can regularly monitor forces in PT tendon/stays/anchors even from a remote access

CONCLUSIONS- Cont'd

Durability

DYNA Force system is robust

Requires no maintenance & has no moving parts

Similar service life to that of bridge or structure

The accuracy of the force measurement is normally within 1.5% for strand and within 3% for bar for preinstalled sensors.

The accuracy of the in-situ sensor is lower due to some uncertainties during the field winding process and due to non existence of zero stress state.

Sensors have been used in over fifty projects and have proven to be the preferred technique to monitor the forces in steel element in terms of accuracy, its performance, ease in installation, & cost effectiveness.

THANK YOU FOR YOUR ATTENTION